

1. Write a MATLAB program to evaluate  $I = \int_a^b f(x) dx$  using the trapezoidal rule with  $n$  subdivisions, calling the result  $I_n$ . Use the program to calculate the following integrals with  $n = 2, 4, 8, 16, \dots, 512$ .

$$(a) \int_0^1 x^4 \arctan(x) dx \quad (b) \int_0^1 x^{2/3} dx$$

The exact value of the integral in (a) is  $\frac{\pi+1-2\ln(2)}{20}$ . Try to arrange your work so that you never compute the value of the integrand at any point more than once. Analyze empirically the rate of convergence of  $I_n$  to  $I$  by calculating the ratios

$$R_n = \frac{I_{2n} - I_n}{I_{4n} - I_{2n}} \text{ and } p_n = \frac{\log(R_n)}{\log(2)}$$

In part (b) compute the extrapolated approximation to  $I$ ,

$$\tilde{I} = I_{4n} - \frac{(I_{4n} - I_{2n})^2}{(I_{4n} - I_{2n}) - (I_{2n} - I_n)}$$

for  $n = 128$ .

2. Repeat problem 1 using Simpson's rule.
3. Apply the corrected trapezoidal rule to the integral in problem 1(a). Compare the results with those of problem 2 for Simpson's rule.
4. Use Gauss-Legendre integration with  $n = 2, 4, 8$  nodes to the integrals of problem 1. Compare the results with those for the trapezoidal and Simpson methods.
5. Find approximate values of the integrals in problem 1 by computing the Romberg integral  $I_{32}^{(5)}$  where  $I_n^{(0)}$  is the  $n$ -panel trapezoid approximation and

$$I_n^{(k)} = \frac{4^k I_n^{(k-1)} - I_{n/2}^{(k-1)}}{4^k - 1}$$

for  $n$  divisible by  $2^k$ .

6. Use the MATLAB function QUADL to find approximate values of the integrals 1(a) and 1(b).
7. Ex. 5.1, p.183, *Shampine, Allen & Preuss*.
8. The 10 point Newton-Cotes integration rule on  $[0, 1]$  is

$$\int_0^1 f(x) dx \approx \sum_{i=0}^9 w_i f\left(\frac{i}{9}\right)$$

with the  $w_i$  determined by requiring that the rule be exact for  $f(x) = 1, x, x^2, \dots, x^9$ .

- (a) Use MATLAB to find the weights  $w_i$ .
- (b) Apply the rule to the integrals in 1(a) and 1(b). Note the errors.

9. We wish to estimate the value of

$$I = \int_0^{\infty} x^{3/2} e^{-x} dx = \frac{3}{4} \sqrt{\pi}$$

- (a) Truncate the integral and use QUADL on the finite part.
  - (b) Try the transformation  $x = -\ln t$  on this integral and use QUADL on the new integral. (QUADL will complain but will do it.)
  - (c) Use the 2, 4 and 8 point Gauss-Laguerre rules to estimate the integral. compare your results with parts (a) and (b) above.
10. In a standard shell and heat exchanger hot vapor condenses on the tube, maintaining a constant temperature  $T_s$ . If the input is at temperature  $T_1$  and the output must be at temperature  $T_2$ , then the length of tube required is given by

$$L = \frac{m}{\pi D} \int_{T_1}^{T_2} \frac{c_p dT}{h(T_s - T)}$$

(All quantities must be in consistent units.) Here  $T$  is the temperature in °F.

$T_1 = 0^\circ\text{F}$  is the inlet temperature.

$T_2 = 180^\circ\text{F}$  is the desired outlet temperature.

$T_s = 250^\circ\text{F}$  is the condensate temperature.

$m$  is the fluid flow rate = 45,000 lb/hr.

$D$  is the diameter of the tube = 1.032 in.

$c_p$  is the specific heat of the fluid =  $(0.53 + 0.00065T)$  BTU/(lb°F).

$h$  is the local heat transfer coefficient =  $\frac{0.023k}{D} \left(\frac{4m}{\pi D \mu}\right)^{0.8} \left(\frac{\mu c_p}{k}\right)^{0.4}$ .

$k$  is the thermal conductivity of the fluid = 0.153 BTU/(hr ft°F).

$\mu$  is the viscosity of the fluid and has units lb/(ft hr).  $\mu$  varies with temperature so that

T	0	50	100	150	200
$\mu$	242	82.1	30.5	12.6	5.57

Use spline interpolation to define  $\mu$  for other values of  $T$  and calculate the required length of the heat exchanger.

item You will need to use the MATLAB functions SPLINE and QUADL. The answer is about 158.7 ft.